



Configuration MultiLevel

| Description of Components | Part No. | No. of Compartments | | | | |
|---|-------------|---------------------|---|---|---|---|
| | | 3 | 4 | 5 | 6 | 7 |
| MultiLevel human machine interface and CPU | MLMAINDISP2 | 1 | 1 | 1 | 1 | 1 |
| Wet-leg sensor interface for MultiLevel, up to 6 compartments | NM2WET-E | 1 | 1 | 1 | 1 | 2 |
| Input/output interface for NoMix and MultiLevel, up to 6 compartments | NM2IO | 1 | 1 | 2 | 2 | 2 |
| MultiLevel level sensor interface for 6 compartments | MLIF | 1 | 1 | 1 | 1 | 2 |
| MultiLevel digital inclination sensor, connection cable 3.5 m | MLIS | 1 | 1 | 1 | 1 | 1 |
| MultiLevel digital temperature sensor | MLDTS-2 | 3 | 4 | 5 | 6 | 7 |
| Chip card reader for MultiLevel system | CCR | 1 | 1 | 1 | 1 | 1 |
| Cable for NoMix, MultiSeal and MultiLevel, L = 12.5 m | NM2KABEL | 1 | 1 | 1 | 1 | 1 |
| Printer EPSON TM-295, 24 V DC, with mounting plate and 15 m cable | DR-U295 | 1 | 1 | 1 | 1 | 1 |
| Wet-leg sensor for NoMix and MultiSeal, with mounting accessories, weld-in nozzle aluminium | NS-2F | 3 | 4 | 5 | 6 | 7 |
| Solenoid valve 3/2-way, dual, 12 V DC, EEx m II T5, cable length 3 m, with emergency manual override | QMV2D | 3 | 4 | 5 | 6 | 7 |
| MultiLevel level sensor, length L = xxxx mm. | MLDSBOxxxx | 3 | 4 | 5 | 6 | 7 |
| Installation kit for MultiLevel x compartments, installation as per drawing 21.251579, excl. welding flange | KMLMSU-xK | 3 | 4 | 5 | 6 | 7 |
| Loading and discharge coupling 4" API, with external pneumatic actuator | VKV1PA | 3 | 4 | 5 | 6 | 7 |

Options:

| | | | | | | |
|--|------------|---|---|----|----|----|
| Weld-in flange for level sensor installation (aluminium) | 251588 | 6 | 8 | 10 | 12 | 14 |
| Weld-in boss (aluminum) for wet-leg sensor NS-2x | 23647 A | 3 | 4 | 5 | 6 | 7 |
| Weld-in boss (steel) for wet-leg sensor NS-2x | 252154 | 3 | 4 | 5 | 6 | 7 |
| Man machine interface (Display) for NoMix and MultiSeal SPD | NM2DISPLAY | 1 | 1 | 1 | 1 | 1 |
| Communication interface EMIS2 for MultiFlow, NoMix, MultiSeal and MultiLevel | EMIS2 | 1 | 1 | 1 | 1 | 1 |
| Printer STAR TM298 24V DC, with mounting plate and 15 m cable | DR-298 | 1 | 1 | 1 | 1 | 1 |