

The **Smith Meter® Model VSC-13 Meter** is a 2", vertical single-case, straight-through type, rotary vane, positive displacement meter. Applications include: blending, batching, dispensing, inventory control, and custody transfer of oils, solvents, chemicals, paints, fats, and fertilizers.

Features

- **Vertical Housing Design** – Facilitates in-line vertical installation while retaining proven Smith Meter® rotary vane design.
- **Superior Accuracy** – Since the unrestricted flow path results in minimal pressure drop across the measuring chamber, slippage through meter clearances is minimized and accuracy maximized.
- **Low Pressure Drop** – Low velocities and streamlined flow path provides the lowest pressure drop PD meter in the industry.
- **Long Service Life** – Low friction ball bearings, fixed cam-type timing, and rugged construction give sustained accuracy and long service life.
- **Extended Flow Turndown** – NCWM approved for use from 3 to 150 GPM; an ideal solution for biofuel blending (see NTEP Certificate 95-054A4).

Operating Specifications

Maximum Flow Rate

	USGPM	L/min
Continuous Rating – Standard Trim	125	475
Intermittent Rating ¹ – Standard Trim	150	570

Minimum Flow Rate – Typical Performance

Linearity ²	Units	Viscosity (Centipoise – cP)					
		0.5	1	5	20	100	400
±0.15%	USGPM	25	15	6	0.15	0.30	0.08
	L/min	95	57	23	6.0	1.00	0.30
±0.25%	USGPM	17	10	4	1.0	0.20	0.05
	L/min	65	38	15	4.0	0.75	0.20
±0.50%	USGPM	13	8	3	0.8	0.16	0.04
	L/min	50	30	11	3.0	0.60	0.15



2" Model VSC-13 Meter

Repeatability

±0.02%

Viscosity

Standard: 400 cP (2,000 SSU) maximum.

Optional: 2,000 cP (10,000 SSU) maximum – specify "High Viscosity Meter Clearances."

Over 2,000 cP: Specify "High Viscosity Meter Clearances" and derate maximum flow rate in direct proportion to viscosity over 2,000 cP (e.g., at 4,000 cP, derate maximum flow rate to 50% of normal continuous rating - 63 USGPM).

Temperature

-20°F to 150°F (-29°C to 65°C).

For other temperatures, consult factory.

Maximum Working Pressure

Standard: 150 psig (1,034 kPa) up to 200°F (93°C).

Meter Gearing

5 U.S. Gallons or 1 Dekalitre per revolution of meter calibrator output shaft.

¹ Intermittent rating applies to service on clean, refined products where continuous operation is not required (e.g., truck loading, rail loading, and other batching applications).

² Based on a maximum flow rate of 125 USGPM (475 L/min).

Ordering Information

Application	Batching, Loading, Blending, Inventory, Process Control, etc.
Operating Conditions	Liquid – Name and sp. gr., Flow Range ⁴ , Temp. Range ⁴ , Viscosity Range ⁵ , Maximum Working Pressure.
Direction of Flow	Vertical upward.
Options & Accessories	As required.

Accessories

Strainer

2" basket-type, Class 150 ANSI raised face flanges⁶.

Set-Stop Valve

Smith Meter® 2" Model 210 Standard or RP (Reduced Port) Digital Electro-Hydraulic Set-Stop Valve.

Pulse Transmitters

UPT – Universal Pulse Transmitter – High resolution dual pulse quadrature output in a weather-tight explosion-proof enclosure (up to 1,000 pulses/rev.).

⁴ Specify: minimum/normal/maximum.

⁵ Standard seals supplied unless optional material specified.

Revisions included in SS01111 Issue/Rev. 0.1 (4/10):

Page 2: Footnote 3 revised.

Figure 4 revised - .50" NPT 2x added.

Page 3: Footnote 6 removed.

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

Contact information is subject to change. For the most current contact information, visit our website at www.fmctechnologies.com/measurementsolutions and click on the "Contact Us" link in the left-hand column.

Headquarters:

500 North Sam Houston Parkway West, Suite 100, Houston, TX 77067 USA, Phone: +1 (281) 260 2190, Fax: +1 (281) 260 2191

Gas Measurement Products:

Erie, PA USA +1 (814) 898 5000

Ellerbek, Germany +49 (4101) 3040

Thetford, England +44 (1842) 822900

Kongsberg, Norway +47 (32) 28 67 00

Buenos Aires, Argentina +54 (11) 4312 4736

Integrated Measurement Systems:

Corpus Christi, TX USA +1 (361) 289 3400

Kongsberg, Norway +47 (32) 28 67 00

San Juan, Puerto Rico +1 (787) 772 8100

United Arab Emirates, Dubai +971 (4) 883 0303

Liquid Measurement Products:

Erie, PA USA +1 (814) 898 5000

Los Angeles, CA USA +1 (310) 328 1236

Ellerbek, Germany +49 (4101) 3040

Slough, England +44 (1753) 571515

Barcelona, Spain +34 (93) 201 0989

Moscow, Russia +7 (495) 5648705

Melbourne, Australia +61 (3) 9807 2818

Beijing, China +86 (10) 6500 2251

Singapore +65 6861 3011

Chennai, India +91 (44) 450 4400

Visit our website at www.fmctechnologies.com/measurementsolutions